

GOVERNMENT OF TELANGANA STATE DISASTER RESPONSE & FIRE SERVICES DEPARTMENT NO OBJECTION CERTIFICATE



From
The Director General
State Disaster Response and Fire Services,
Telangana, Hyderabad.

To, SR. DR. JESY K. VARGHESE, Mother Mary Convent, Mariagri shrine, R.P Road, Nalgonda,

	Rc. No.173460002019Dated:13/09/2019
Sir,	
Sub:	TELANGANA STATE DISASTER RESPONSE & FIRE SERVICE DEPARTMENT –.
	Issue of No Objection Certificate for Occupancy to the Non Multi storeyed Building of ST MARY'S UPPER PRIMARY SCHOOL, SY. NO. 43, CHERLPALLY, NALGONDA,
	TELANGANA-508001 Cherlapally, Nalgonda, 508001/- Cherlapalle/Nalgonda/Nalgonda, Hyderabad – Regarding.
Ref:	 Acknowledgement No173460002019dt.13/09/2019 This Office Provisional NOC RC No.173460002019dt.13/09/2019 Inspection Committee Report,.
Paul :	Hyderabad Rc. No. 173460002019, dt. 13/09/2019



The Multi Storeyed Building Inspection committee, vide reference cited (3) have inspected the Non Multi Storeyed Building of ST MARY'S UPPER PRIMARY SCHOOL, SY. NO. 43, CHERLPALLY, NALGONDA, TELANGANA-508001 Cherlapally, Nalgonda, 508001/-Cherlapalle/Nalgonda/Nalgonda on ------and submitted the following report.

2. The builder was issueed Provisional No Objection certificate vide reference cited (2) for construction of Non Multi Storeyed Building 1 Ground, 2 Floors, with for Occupancy (). Now the builder has constructed Non Multi Storeyed Building with 1 Ground, 2 Floors, with a height of 11.50 Meters for EDUCATIONAL B-1 Schools up to senior secondary level Occupancy () and requested for No Objection Certificate for Occupancy.

3. Open Spaces: The builder provided the following open spaces all around the building.

Sl.No side		de Open space Required as per Provisional No Objection Certificate	
1	FRONT	6.00	50.00
2	REAR	6.00	6.00
3	Side-1	6.00	10.00
4	Side-2	6.00	36.00
5	Front Direction		

4. Means of Access:

Sl. No	Gate Width As per NBC 2016	Required	Provided	
1	Entry gate width	4.50	6.00	
2	Exit Gate Width	4.50	6.00	
3	Entry Gate Head Clearance	5.00	5.00	
4	Exit Gate Head Clearance	5.00	5.00	

5. Travel Distance

SI. No.	Item / Description	Required (Not More than in Mtrs.)	Provided
1	Farthest point (Most Remote Point) With in a storey or a mezzanine floor to the door to an Exit.	30.00	28.00
2	The Dead end of the corridor length in exit access. (6 mtrs for Educational, Institutional and Assembly, 15mtrs for other Occupancies)	6.00	6.00
	PRINCIPAL.	Correspondent	nertick.

PRINCIPAL
ST. MARY'S SCHOOL
Opp: 12th Battalion, Vidya Nagar,

ST. MARY'S SCHOOL

Opp. 12th Battalion, Vidya Nagar, Hyd. Road, Cherlapally, P.O. Nalgoods T

Sl.no.	Type of staircases	Width (In Mtrs)	No of staircases	Floors from	Floors to
1	Internal staircases	1.50	1	Ground	2nd Floor
2	External staircases	1.50	1	Ground	2nd Floor

7. Means of Escape Floor Wise Details

Sl.no	Floor type	Buil-up Area in Sq.Mtrs	Type of Occupancy	Occupan t Load	Means of escape required as per table 21 of NBC	Means of escape Provided
1	Groun d	526.40	EDUCATIONAL B-1 Schools up to senior secondary level	132.00	2.63	3.00
2	1st Floor	526.40	EDUCATIONAL B-1 Schools up to senior secondary level	132.00	2.63	3.00
3	2nd Floor	526.40	EDUCATIONAL B-1 Schools up to senior secondary level	132.00	2.63	3.00

8. Floor Wise details of Fire Fighting Installations.

Sl.n o	Floor Details	Fire Extinguish er	Hose Reel	Automatic Sprinklers System	Manually Operated Electronic Fire Alarm System	Automatc detection and alarm system
1	Ground	3.00	1.00	0.00	0.00	0.00
2	1st Floor	3.00	1.00	0.00	0.00	0.00
3	2nd Floor	3.00	1.00	0.00	0.00	0.00

9. Fire Fighting Installations as per Table 7 of NBC 2016:

Fire Fighting System.	Required As per NBC	Provided
Fire Extinguishers	9.00	12
First Aid Hose Reel	3.00	3
Terrace Tank over Respective Tower Terrace in Litres	10000,00	10000
Pump Capacity in LPM at the Terrace Tank Level with Minimum Pressure of 3.5 kg/cm ²	450.00	450

10. The builder has provided the following additional Fire Safety Requirements as per NBC of India 2016 as per NBC part 4 of India 2016::

SI.

N Fire safety Item

0

- 1. Open spaces all around the building are Leveled and have hard open spaces for the operation of fire vehicles.
- 2. The upper floors of the educational building are provided with exits for every travel distance of 30 meters (TYPE1 & 2 constructions) as per table5 under clause 4.4.2.1, 4.4.2.2 of Part IV of NBC 2016
- 3. The width of all exit door ways has 01-00 meter for class rooms and 02-00 meters in respect of Assembly halls as per clause 8.1 of IS 14435:1997?
- 4. The height of exit door ways has 02-00 meters and more, as per clause of 8.2 of IS 14435:1997?
- 5. A minimum number of two separate exits are provided for each floor as per clause 6.2 of IS 14435:1997?
- 6. The exits shall be remote from each other as practicable as per clause 6.2 of IS 14435:1997?
- 7. 02 Doorways are provided for every room with a capacity of over 45 persons As per clause 6.2.2(a) of part-IV of NBC-2016
- The Location of Rooms of Preschool, Kindergarten, Class/Grade 1 student are provided at Ground Floor/level and Class/Grade II student at ground or First Floor only.
 - The building is suitably Compartmented and provided with smoke control measures so that fire / smoke remain
- confined to the area where fire incident has occurred and does not spread to the remaining part of the building as per Clause 4.5 and 4.6 of part 4 NBC of India 2016.

Floor Openings Fire Protection Complied with As per Clause 3.4.5.4

a) Openings in Service ducts and shafts allowing building services like cables, Electrical wirings, Telephone cables,

Correspondent

ST. MARY'S SCHOOL
Opp: 12th Battalion, Vidya Nagar,
Hud Road Charlanally P.O. Nalgonda T.S.

ST. MARY'S SCHOOL
Opp. 12th Battalion, Vidya Nagar,
Hyd. Road Characteristics

İ	plumbing pipes etc., shall be protected	by enclosure in the form of du	cts / shaft having a fire resistant's not less than
	e) For plumbing shafts in the core of the inspection doors having fire resistance	rating not less than 30 min	ening inside the building, the shafts shall have
	Vertical openings Fire Protection Confloors of a building shall be suitably enally as a Reasonable safety to the occupants through vertical openings from floor to Further it shall be ensured to provide a b) Limitation of damage to the building	mplied with as per Clause-3 neclosed or protected, as necessary while using the means of egress of floor to allow occupants to conclude the period of 2 100 mm in the conclude the period of 2 100 mm in the conclude the period of 2 100 mm in the conclude the period of 2 100 mm in the conclusion.	s by preventing spread of fire, smoke, or fumes
12	Electrical safety complied with as po	CONTRACTOR	C of India 2016
-	d) all metallic items like steel structura		
13	Routing of down conductors (insulated shafts are not allowed as it can create it Section 2 Electrical and Allied Installa Escape Lighting and Exit Signage is	Complied with as per clause - f or uninsulated) of lightning pr ire and explosion during lightn tions' of the Code Complied with as per Clause	-3.4.6.5 rotection through electrical or other service ing. For details, see Part 8.Building Services,
	exit access, exits and exit discharge sh of the egress systems so that all occupa	all be properly identified, with ants shall be able to leave the fa	adequate lighting maintained in the elements
	Lighting is Complied with as per Cla		
	landings of stairwells and exit.	, including angles and intersect	d continuously. The floors of the means of ions, in corridors and passageways, stairwells,
	min in the event of failure of the norma	vided to be put on within 5 s of to maintain the required illuminal lighting even for smaller pres	the failure of the normal lighting supply, nation level for a period of not less than 90 mises
	 d) Signs are required at all exits, emerged requirements of the relevant Indian Sta 	ency exits and escape routes, with a second	which should comply with the graphic
	Number of exits, Arrangements of exit complied with Clause 4.4.2 of part – 4	s and capacities of Means of eg NBC of India 2016	ress types of exit access and exits etc.,
12	Smoke control of exits are complied w	and the second s	SC of India 2016
	Fire Drills and Fire orders Complied w		
19	the event of fire and other emergency. ' event of emergency, by displaying fire should be displayed prominently in bol rise buildings, see Annex D	fulfil the requirements of firefi The occupants shall be made the notices at vantage points and all d lettering. For guidelines for fi	ghting and evacuation from the buildings in oroughly conversant with their action in the so through regular training. Such notices are drills and evacuation procedures for high
22	Clause 3.1 of part – 4 NBC of India 20	16	e tanks and pump house are Complied with
	Fire Safety plans prepared and submitte	ed by the builder.	
	2016.	once in 6 months as per Clause	at least once in every 03 months for building e D-3 in annex. D of Part IV NBC of India
l 1) Obj vith	In view of the above and as per recommection Certificate for occupancy is issued.	nendations of the multistoried bed to Multi Storied Building	ouilding inspection Committee, the No
	As Builder	As occupant	As Security Personnel
	-All the fire protection		
l	arrangements shall be maintained in good condition as seen during inspection.	All the escape/exit roots shall not be kept locked/blocked or encroached	All the occupants must know the correct method of operation of the fire fighting
	-Do's and Dorff to case of fire	Control of the contro	system installed. Correspondent
	PRINCIPAL ST. MARY'S SCHOOL Opp: 12 th Battalion, Vidya Nagar, Hyd Road, Cherlapally P.O. Nalgonda. T.S.		ST. MARY'S SCHOOL Opp. 12th Battalion, Vidya Nagar, Hyd. Road, Cherlapathy BO Malanda

	shall be prominently displayed in entire building	DIVERSITATION TO THE TANK TO SERVE THE SERVE T	
2	Any loss of life or property due to non-functioning of fire safety measures and other installations shall be the responsibility of the management.	All occupants shall be trained to operate the fire safety equipments during emergency.	Mock drills should be conducted once in 3 months for initial two years. Thereafter, once in every 6 months.
3	Addition / alteration, if any in the building may be verified by building authority.	Mock drills should be conducted once in 3 months for initial two years. Thereafter, once in every 6 months.	All security personnel shall be trained to operate the fire safety equipments during emergency and guiding the occupants in safe evacuation. Call the fire Brigade by dialing 101.
4	This No objection Certificate for occupancy is valid for five year from the date of issue of this letter.	Raise the alarm if the fire cannot be controlled, evacuate the area completely at once from the nearest safe exit.	Attack the fire using available fire equipment only if you feel capable of controlling it. If Not, take all steps to isolate the area by closing doors and windows.

This No Objection Certificate for Occupancy is valid for Five years from the date of issue of this letter. It is the responsibility of the builder to apply for renewal NOC, duly remitting the user charges as per G.O. Ms. No. 71, Home (Prison – A) Department, dated 01-04-2010, two months before expiry of this No Objection Certificate.

Yours Sincerely, Director General of State Disaster Response & Fire Services Telangana, Hyderabad

Copies to:

i) The Management

ii) Multistoried Building Inspection Committee

PRINCIPAL
ST. MARY'S SCHOOL
Opp: 12th Battalion,Vidya Nagar,
Hyd Road, Cherlapally P.O. Nalgonda. T.S.

Correspondent

ST. MARY'S SCHOOL

Opp. 12th Battalion, Vidya Nagar, Hyd. Road, Cherlapally, P.O. Nalgonda T.S.